

THE NEW C2011 WHITEFISH FILL-ETING MACHINE offers a high and consistent yield, achieved by a robust and reliable design specific for white-fish processing.


Simple user interface allows the operator to easily switch between different species, select different range settings, adjust the machine speed and operate the machine safely.

Opening the safeguards provides a clear and easy access to the machine internals, minimizing the time required for daily maintenance, cleaning and repair work.

Automatic lubrication system ensures that all critical parts are well lubricated, reducing repair and maintenance work while providing a reliable and safe operation.

Stainless steel trays, adjustable guides and flexible cutting mechanism ensure high and consistent yield and throughput.

All materials used, in direct contact with the processed fish have been carefully selected to be approved for food processing.



THE NEW C-2011 WHITEFISH FILLETING MACHINE OFFERS A HIGH AND CONSISTENT YIELD, ACHIEVED BY A ROBUST AND RELIABLE DESIGN SPECIFIC FOR WHITEFISH PROCESSING.





FILLETTING MACHINE C2011

MACHINE APPLICATION



The operator places the fish on to a saddle which transports the fish through each processing area of the machine where the meat is separated from the bones. The machine delivers the two fillets ono separate conveyors leading from the machine while delivering the bones separately.

MACHINE RANGE

Filleting Machine (small)

- 1. Haddock (700g 2.8kg)
- 2. Atlantic Cod (700g 3kg)
- 3. Pacific Cod (700g 2.5kg)
- 4. Pollack (700g 2.8kg)
- 5. Tusk (700g 2.8kg)
- 6. Ling (700g 2.8kg)
- 7. **Sea Wolf** (1kg 2.5kg)

Filleting Machine (medium)

- 1. Haddock (2kg 4kg)
- 2. Atlantic Cod (2kg 5kg)
- 3. Pacific Cod (2kg 4kg)
- 4. Pollack (2kg 4kg)
- 5. Tusk (2kg 4kg)
- 6. Ling (2kg 4kg)
- 7. Sea Wolf (2 4kg)

Filleting Machine (large)

- 1. Haddock (2.8kg 5kg)
- 2. Atlantic Cod (2.8kg 12kg)
- 3. Pacific Cod (2.8kg 8kg)
- 4. Pollack (2.8kg 8kg)
- 5. Tusk (2.8kg 8kg)
- 6. Ling (2.8kg 8kg)
- 7. Sea Wolf (2.8kg 8kg)

GENERAL SPECIFICATIONS

Type: Filleting Machine.

Throughput: 16 - 38 fishes/min Conveyor Speed: 30m/min Knife Speed: 1100 rpm.



DIMENSIONS

Length: 4.060m Width: 1.880m Height: 2.25 - 2.35m

ELECTRICAL

Input Voltage: 3phase 380-440V AC. Power Rating: 4.5kW (6hp)

WATER

Normal Flow: 800-1600l/h

